CLEAN VERSION OF THE ENTIRE SET OF CLAIMS

1   1.   A method comprising:

2   determining a processor state of a processor upon expiration of a system

3   management interrupt (SMI) timer, the processor state being one of an operational state

4   and a low power state;

5   loading the SMI timer with a timer value based on the processor state, the timer

6   value being one of a first value and a second value; and

7   transitioning the processor to one of the operational state and the low power state

8   according to the processor state.

1   2.   The method of claim 1 wherein loading the SMI timer comprises:

2   loading the SMI timer with the first value if the processor state is the operational

3   state; and

4   loading the SMI timer with the second value if the processor state is the low power

5   state.

1   3.   The method of claim 2 wherein transitioning comprises:

2   transitioning the processor to the operational state if the processor state is the low

3   power state; and

4   transitioning the processor to the reduced power state if the processor state is the

5   operational state.

1   4.   The method of claim 1 further comprising:

2   disabling the SMI timer if throttling is disabled; and

3   enabling the SMI timer if throttling is enabled.

1   5.   The method of claim 1 further comprising:

2   generating a SMI access to a throttling state in response to an input/output (I/O)

3   trap;

4   updating the throttling state if the access is a write; and

5   returning the throttling state if the access is a read.

1   6.   The method of claim 5 wherein generating the SMI access comprises:

2   reporting the throttling state at a dummy address; and

3   generating the I/O trap by an SMI handler using the dummy address, the I/O trap

4   generating the SMI access.

1   7.   The method of claim 6 wherein generating the I/O trap comprises:

2   invoking the SMI handler to trap on the dummy address;

3   booting a power management OS;

4   loading the dummy address by the power management OS;

5   accessing the throttling state at the dummy address by the power management OS;

6   and

7   generating the I/O trap by a chipset in response to accessing the throttling state by

8   the power management OS.

1   8.   The method of claim 4 wherein booting the power management OS

2   comprises:

3   booting an Advanced Configuration and Power Interface (ACPI) OS.

1   9.   The method of claim 3 wherein transitioning the processor to the low power

2   state comprises:

3   transitioning the processor to one of a first power state, a second power state, a

4   third power state, and a sleep state.

1   10.   The method of claim 1 wherein loading the SMI timer comprises:

2   loading the SMI timer in a chipset.

1   11.   A computer program product comprises:

2   a machine useable medium having computer program code embedded therein, the

3   computer program product having:

4   computer readable program code to determine a processor state of a

5   processor upon expiration of a system management interrupt (SMI) timer, the

6   processor state being one of an operational state and a low power state;

7   computer readable program code to load the SMI timer with a timer value

8   based on the processor state, the timer value being one of a first value and a second

9   value; and

10   computer readable program code to transition the processor to one of the

11   operational state and the low power state according to the processor state.

1   12.   The computer program product of claim 11 wherein the computer readable

2   program code to load the SMI timer comprises:

3   computer readable program code to load the SMI timer with the first value if the

4   processor state is the operational state; and

5   computer readable program code to load the SMI timer with the second value if the

6   processor state is the low power state.

1   13.   The computer program product of claim 12 wherein the computer readable

2   program code to transition comprises:

3   computer readable program code to transition the processor to the operational state

4   if the processor state is the low power state; and

5   computer readable program code to transition the processor to the reduced power

6   state if the processor state is the operational state.

1   14.   The computer program product of claim 11 further comprising:

2   computer readable program code to disable the SMI timer if throttling is disabled;

3   and

4   computer readable program code to enable the SMI timer if throttling is enabled.

1   15.   The computer program product of claim 11 further comprising:

2   computer readable program code to generate a SMI access to a throttling state in

3   response to an input/output (I/O) trap;

4   computer readable program code to update the throttling state if the access is a

5   write; and

6   computer readable program code to return the throttling state if the access is a read.

1   16.   The computer program product of claim 15 wherein the computer readable

2   program code to generate the SMI access comprises:

3   computer readable program code to report the throttling state at a dummy address;

4   and

5   computer readable program code to generate the I/O trap by an SMI handler using

6   the dummy address, the I/O trap generating the SMI access.

1   17.   The computer program product of claim 16 wherein the computer readable

2   program code to generate the I/O trap comprises:

3   computer readable program code to invoke the SMI handler to trap on the dummy

4   address;

5   computer readable program code to boot a power management OS;

6   computer readable program code to load the dummy address by the power

7   management OS;

8   computer readable program code to access the throttling state at the dummy address

9   by the power management OS; and

10   computer readable program code to generate the I/O trap by a chipset in response

11   to accessing the throttling state by the power management OS.

1   18.   The computer program product of claim 14 wherein the computer readable

2   program code to boot the power management OS comprises:

3   computer readable program code to boot an Advanced Configuration and Power

4   Interface (ACPI) OS.

1   19.   The computer program product of claim 13 wherein the computer readable

2   program code to transition the processor to the low power state comprises:

3   computer readable program code to transition the processor to one of a first power

4   state, a second power state, a third power state, and a sleep state.

1   20.   The computer program product of claim 11 wherein the computer readable

2   program code to load the SMI timer comprises:

3   computer readable program code to load the SMI timer in a chipset.

1   21.   A system comprising:

2   a processor;

3   a memory coupled to the processor to store a throttling emulator, the throttling

4   emulator, when executed, causing the processor to:

5   determine a processor state of the processor upon expiration of a

6   system management interrupt (SMI) timer, the processor state being one of an

7   operational state and a low power state;

8   load the SMI timer with a timer value based on the processor state,

9   the timer value being one of a first value and a second value; and

10   transition the processor to one of the operational state and the low

11   power state according to the processor state.

1   22.   The system of claim 21 wherein the throttling emulator causing the

2   processor to load causes the processor to:

3   load the SMI timer with the first value if the processor state is the operational state;

4   and

5   load the SMI timer with the second value if the processor state is the low power

6   state.

1   23.   The system of claim 22 wherein the throttling emulator causing the

2   processor to transition causes the processor to:

3   transition the processor to the operational state if the processor state is the low

4   power state; and

5   transition the processor to the reduced power state if the processor state is the

6   operational state.

1   24.   The system of claim 21 wherein the throttling emulator, when executed,

2 further causes the processor to:

3   disable the SMI timer if throttling is disabled; and

4   enable the SMI timer if throttling is enabled.

1   25.   The system of claim 21 wherein the throttling emulator further causes the

2 processor to:

3   generate a SMI access to a throttling state in response to an input/output (I/O) trap;

4   update the throttling state if the access is a write; and

5   return the throttling state if the access is a read.

1   26.   The system of claim 25 wherein the throttling emulator causing the

2 processor to generate the SMI access causes the processor to:

3   report the throttling state at a dummy address; and

4   generate the I/O trap by an SMI handler using the dummy address, the I/O trap

5 generating the SMI access.

1   27.   The system of claim 26 wherein the throttling emulator causing the

2 processor to generate the I/O trap causes the processor to:

3   invoke the SMI handler to trap on the dummy address;

4   boot a power management OS;

5   load the dummy address by the power management OS;

6   access the throttling state at the dummy address by the power management OS; and

7   generate the I/O trap by a chipset in response to accessing the throttling state by the

8 power management OS.

1   28.   The system of claim 24 wherein the throttling emulator causing the

2 processor to boot the power management OS causes the processor to:

3   boot an Advanced Configuration and Power Interface (ACPI) OS.

1   29.   The system of claim 23 wherein the throttling emulator causing the

2   processor to transition the processor to the low power state causes the processor to:

3   transition the processor to one of a first power state, a second power state, a third

4   power state, and a sleep state.

1   30.   The system of claim 21 wherein the throttling emulator causing the

2   processor to load the SMI timer causes the processor to:

3   load the SMI timer in a chipset.